

DESCRIPTION

Classic Coat is a line of OEM matched aerosols for renewing or restoring leather and vinyl.

FEATURES

- Excellent for vinyl and leather
- Superior adhesion, flexibility and hiding
- Will not crack
- Quick drying
- Simple to use

SUITABLE SUBSTRATES

- Vinyl
- Leather

TYPICAL PROPERTIES

| Part: | Product Name: | Color: | Container: |
|-------|---------------|-------------------|----------------|
| 17363 | Classic Coat | Lt. Graystone | 16 oz. Aerosol |
| 17373 | Classic Coat | Dk. Slate Gray | 16 oz. Aerosol |
| 17383 | Classic Coat | Med. Lt. Stone | 16 oz. Aerosol |
| 17393 | Classic Coat | Lt. Stone | 16 oz. Aerosol |
| 17403 | Classic Coat | Camel | 16 oz. Aerosol |
| 17413 | Classic Coat | Lt. Cashmere | 16 oz. Aerosol |
| 17423 | Classic Coat | Med. Cashmere | 16 oz. Aerosol |
| 17433 | Classic Coat | Very Dk. Cashmere | 16 oz. Aerosol |
| 17503 | Classic Coat | Limo Flat Black | 16 oz. Aerosol |
| 17013 | Classic Coat | Midnight Black | 16 oz. Aerosol |
| 17023 | Classic Coat | Lt. Graphite | 16 oz. Aerosol |
| 17033 | Classic Coat | Lt. Parchment | 16 oz. Aerosol |
| 17043 | Classic Coat | Med. Graphite | 16 oz. Aerosol |
| 17053 | Classic Coat | Med. Parchment | 16 oz. Aerosol |
| 17063 | Classic Coat | Med. Prarie Tan | 16 oz. Aerosol |
| 17073 | Classic Coat | Med. Dk. Graphite | 16 oz. Aerosol |
| 17083 | Classic Coat | Dk. Graphite | 16 oz. Aerosol |
| 17093 | Classic Coat | Black | 16 oz. Aerosol |
| 17103 | Classic Coat | Dk. Gray | 16 oz. Aerosol |



Check local VOC regulations to ensure compliance of all products in your area.

| | | | |
|-------|--------------|-----------------|----------------|
| 17113 | Classic Coat | Graphite | 16 oz. Aerosol |
| 17123 | Classic Coat | Lt. Gray | 16 oz. Aerosol |
| 17133 | Classic Coat | Lt. Neutral | 16 oz. Aerosol |
| 17143 | Classic Coat | Lt. Oak | 16 oz. Aerosol |
| 17163 | Classic Coat | Med. Dk. Pewter | 16 oz. Aerosol |
| 17173 | Classic Coat | Med. Gray | 16 oz. Aerosol |
| 17183 | Classic Coat | Med. Neutral | 16 oz. Aerosol |
| 17203 | Classic Coat | Shale | 16 oz. Aerosol |
| 17213 | Classic Coat | Very Dk. Gray | 16 oz. Aerosol |
| 17223 | Classic Coat | Very Dk. Pewter | 16 oz. Aerosol |
| 17243 | Classic Coat | Taupe | 16 oz. Aerosol |
| 17263 | Classic Coat | Classy Gray | 16 oz. Aerosol |
| 17293 | Classic Coat | Ivory | 16 oz. Aerosol |
| 17313 | Classic Coat | Tan | 16 oz. Aerosol |
| 17323 | Classic Coat | Creamy Ivory | 16 oz. Aerosol |
| 17353 | Classic Coat | Silver Gray | 16 oz. Aerosol |

| | |
|--------------------------|------------------------|
| Coats: | 2-3 |
| MIR: | Category VFL < 1.55 |
| Cure time: | 24 hours @ 70°F (21°C) |
| Coverage per Can: | 10 ft ² |

Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION



PREPARATION:

VINYL:

1. Clean first with SEM Soap and a gray scuff pad, paying close attention to textured or recessed areas. Rinse with water or wipe off with a clean, damp, lint-free towel.
2. Clean thoroughly with Vinyl Prep using a clean, damp, lint free towel and wiping in one direction or apply **XXX Universal Surface Cleaner**. Rinse with water and dry or wipe off with a clean, damp, lint-free towel. If contamination still exists, water will bead on the surface. Repeat this step until beading no longer occurs.



Check local VOC regulations to ensure compliance of all products in your area.

LEATHER:

1. Clean with SEM Soap and a gray scuff pad, paying close attention to textured or recessed areas. Wipe with a clean damp towel to remove all residue and allow surface to dry.
2. Clean with Plastic & Leather Prep or **XXX Universal Surface Cleaner**.
3. When dry, scuff the leather with a clean, gray scuff pad or 400-600 grit sandpaper.
4. Clean again with Plastic & Leather Prep or **XXX Universal Surface Cleaner**.



MIXING:

Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).



APPLICATION:

Apply light coats, allowing 5-10 minutes between coats. Even though film is dry to touch, the substrate should not be subjected to heavy abuse or abrasion for 24 hours.

Note: Spray tip may be adjusted for either a vertical or horizontal fan spray pattern.

If clogging develops, remove spray button with a twisting motion and clean with **XXX Universal Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.



After each use, turn can upside down and spray several seconds to clear spray tip.



STORAGE:

Classic Coat should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for Classic Coat is 3 years when stored under normal conditions.

RELATED PRODUCTS:

| Part: | Product Name: | Size: |
|-------|-------------------------------|----------------|
| 38343 | Vinyl Prep | 16 oz. Aerosol |
| 38344 | Vinyl Prep | Quart |
| 38351 | Plastic & Leather Prep | Gallon |
| 38353 | Plastic & Leather Prep | 16 oz. Aerosol |
| 38354 | Plastic & Leather Prep | Quart |
| 39362 | SEM Soap | Pint |
| 77771 | XXX Universal Surface Cleaner | Gallon |
| 77774 | XXX Universal Surface Cleaner | Quart |
| 77763 | XXX Universal Gun Cleaner | 20 oz. Aerosol |



Check local VOC regulations to ensure compliance of all products in your area.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.